
SPECIFICATION SHEET

Serenity Figura Arch Mirror Cabinet 600mm Left Hand Hinge Door


Newtech Code: 95130L

Features

- Arch Mirror Cabinet
- Dimensions: H1000 x W600 x D129
- Four Internal Shelves
- Soft Close Mirror Door
- Left Hand Hinge
- Demister Upgrade Available - Add [DM] to cabinet code ie. 95130LSWDM
- Able to be recessed into the wall




Technical Details



TOP VIEW

FRONT VIEW

SIDE VIEW



TOP VIEW with demister

FRONT VIEW with dem

SIDE VIEW with demister

Notes:

All measurements shown are in millimetres. Sizes are nominal.

newtech LIVING — BATHROOMS

Head Office: 30 Mill Road, Wanganui
Phone: 0800 728 662
www.newtech.co.nz/bathrooms

Head Office & Manufacturing plant | 30 Mill Road, Wanganui
Phone: 06 349 0194 or 0800 728 662, sales@newtech.co.nz

Mirror Cabinet Demister

Specification & Installation Instructions

Newtech Living recommends that a registered electrician install this product and that it is installed to the current wiring regulations and in particular to those regulations that include the installation of appliances and accessories in damp environments such as bathrooms. It must be installed in accordance with relevant Australian/New Zealand Standards (AS/NZS).

The Mirror Demister is designed to leave mirrors mist free and clear.
The mirror demister should be operated for a few minutes before turning on the shower or running a bath.

Sizing Guide

Mirror Size	Demister Size	Demister Required	Watts
450mm	310mm x 450mm	One	2.5W/dm2
600mm	310mm x 450mm	One	2.5W/dm2
750mm (Demister on Large Mirror Door)	310mm x 450mm	One	2.5W/dm2
900mm (Demister on Centre Mirror Door)	310mm x 450mm	One	2.5W/dm2
1200mm (Demister on Centre Mirror Door)	310mm x 450mm	One	2.5W/dm2
1500mm (Demister on Centre Mirror Door)	310mm x 450mm	One	2.5W/dm2
1800mm (Demister on Centre Mirror Door)	310mm x 450mm	One	2.5W/dm2

INSTALLATION INSTRUCTIONS - WIRING INTO THE WALL

1. Mirror must be wired through a 230V isolation switch, either independently or combined with lighting.

2. Mirror is supplied with 600mm twin flex cable measured from outlet in mirror door.

3. Depending on mirror placement, the flex cable is located on bottom left for left hand hinged mirror doors and top right for right hand hinged mirror doors. For 450mm, 600mm and 750mm sized mirrors, the demister is located on the outside door and for the 900mm and 1200mm sized mirrors the demister is located on the middle door.

Note: Newtech fit the mirror demister for an additional charge when purchasing an Avon or Kolum Mirror cabinet, and must be ordered at time of purchase.

IMPORTANT: Please note a registered electrician is required to complete all wiring installation and connections. It is recommended the mirror is wired through an RCD (Residual-current device).